



HEIGHT OF SIGN TO BE DETERMINED BASED ON FINAL LOCATION

- ROUND STEEL POST CAPS FASTENED WITH WEATHER RESISTANT LAG SCREWS. COLOUR TO MATCH BRACKETS AND FRAME.
- 2 PIECE ROUND STEEL MOUNTED BRACKET C/W BOLTS AND FLANGE TO ACCEPT SIGN FRAME. BLUE PAINT TO MATCH SIGN FRAME.
- DOUBLE SIDED ALUMINUM PANEL WITH CREAM COLOUR VINYL BACKGROUND, BLUE TEXT AND COLOURED LOGO. COLOURS TO MATCH TOWNSHIP OF SELWYN BRANDING SPECIFICATIONS.
- BLUE ALUMINUM FRAME WITH FLANGES TO FASTEN TO POST BRACKETS.
- 300mm DIAMETER FINISHED CEDAR OR PINE POSTS. TREAT POSTS WITH PRESERVATIVE FROM GROUND LEVEL DOWN. FINISH POSTS WITH NATURAL WOOD STAIN.
- CONCRETE SONO TUBE - SIZE AND DEPTH TO BE DETERMINED BY STRUCTURAL ENGINEER. TOP OF SONO TUBE +/- 150mm ABOVE GRADE.

- NOTES:
1. SIGN MANUFACTURER TO PROVIDE ENGINEERED STRUCTURAL SHOP DRAWING FOR REVIEW AND APPROVAL.
 2. PROVIDE SIGN LAYOUT COLOUR SAMPLES AND FONT SELECTIONS FOR APPROVAL.
 3. VERIFY CONDITIONS ON SITE AND STAKE LOCATION OF POSTS FOR CLIENT APPROVAL.
 4. SIGN CONTRACTOR RESPONSIBLE FOR ALL PERMITS AND AGENCY APPROVALS.